



PRODUCT CATALOGUE



Shuttering Plywood

- ❖ Uniform Thickness
- ❖ Uniform Weight
- ❖ Zero Water Penetration Film
- ❖ Highly Compressed
- ❖ High Tensile Strength
- ❖ Full Core, Full Panel Of Eucalyptus Of Social Forestry



Farmers wood

- MUF resin is as per BIS standard
- Available variants :
 - 23 kg
 - 25 kg
 - 30 kg

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY

SHAKTIMAN
FILM FACE SHUTTERING PLY



Shaktiman

- MUF resin is as per BIS standard
- Available variants :
 - 23 kg
 - 25 kg
 - 30 kg



Ply Smith

- MUF resin is as per BIS standard
- Available variants :
 - 23 kg
 - 25 kg
 - 30 kg



Solution

- MUF resin is as per BIS standard
- Available variants :
 - 23 kg
 - 25 kg
 - 30 kg



Support

- PF resin is as per BIS standard
- Available variants :
 - 23 kg
 - 25 kg
 - 30 kg
 - 34 kg
 - 50 kg



Bhoomi

- PF resin is as per BIS standard
- Available variants :
 - 23 kg
 - 25 kg
 - 30 kg
 - 34 kg
 - 50 kg



Black Strength

- PF resin is as per BIS standard
- Available variants :
 - 23 kg
 - 25 kg
 - 30 kg
 - 34 kg
 - 50 kg





Terms and Conditions

- 23kg thickness will be 9mm+
- 25kg thickness will be 10mm+
- 30kg thickness will be 11mm+
- 34kg thickness will be 12mm+
- 50kg thickness will be 17mm+



Contact us

Deepak Lamination

Garhi Road, Post Midania

Lakhimpur Kheri, UP, India 262701

Mob: 9415148262, 9983561101

deepaklaminationImp@gmail.com

www.deepaklamination.com